


B8TURBOV

HD 1080p Turbo HD Bullet Camera



epcom
POWERED BY HIKVISION



► Camera

Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	2.8 - 12mm @ F1.4 Angle of view: 92° - 32°
Lens Mount	φ14
Day & Night	ICR
Wide dynamic range	120 dB
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB

► General


Working Temperature/ Humidity	-20°C-60°C(-4°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12 VDC: Max. 4.5W ; 24 VAC: Max. 6.5W
Weather Proof Ratings	IP66
IR Range	Up to 50m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	300.82×100.76×107.55mm (11.84"×3.97"×4.23")
Weight	880 g (1.95 lb)

► Menu

Scene	Indoor, outdoor, indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, japanese, CHN1, CHN2, korean, german, french, italian, spanish, polish, russian, portuguese, dutch, turkish, hebrew and arabic
Function	Eclipse, digital noise reduction, digital zoom (62X), slow shutter, mirror, defog, defect pixel correction, SMART-DZOOM

► Key Features

HD1080p video output
Adopt HDTVl Technology
True Day/Night
2.8 - 12mm vari-focal lens
OSD menu, 3D DNR, SmartIR
Up to 50m IR distance
Up the Coax(via coaxial cable)
120 dB Wide Dynamic Range



Unit:mm